

SMART-30S is Value for Everyone!

www.idp-corp.com

Overlay •

UV Panel ●



Applications

- ID / Membership
- Access control / Security
- Healthcare
- Government
- Banking Card
- Transportation
- Retail
- Gift / Promotion / Loyalty

Features

- Color & Mono Printing
- Transparent Card with Magnetic Stripe
- Full Encoding Support (Magnetic, Contact, Contactless)
- Removable Stacker
- Compact Size



SMART-30S Specifications

SMART-30S (Single Side Card Printer)

Printing

Print Type

Print Area

Print Area

Print Area

O Edge to Edge

Resolution

300 dpi

Dual Side Printing TBD

Card _

Card Feeding OAutomatic

Card Size ////// **ISO CR80 (54mm x 86mm / 2.12" x 3.38")**

Card Thickness /// 0.38mm(15mil) ~ 0.76mm(30mil)

Card Type // OPVC, Composite PVC, PET

Print Speed

Monochrome • 5 sec. (720 cards/hour)

YMCKO • 28 sec. (128 cards/hour)

Capacity

Input Hooper • 80 cards
Output Hooper • 25 cards

System

Memory

Control Panel

Supported Platforms • Microsoft Windows 2000/2003/XP/Vista/7,

Mac OS, Linux

Communication USB, Ethernet (Option)

Power Supply Free Voltage (AC 110/220V, 50~60Hz)

Power Consumption (Max) • 48W

Temperature / Humidity \ ○ 15~35 ℃ / 20~80%

Dimensions

Dimension (WxLxH) 172 mm x 377mm x 190mm

Weight 0 3.4 kg / 7.5 lbs

Encoding Options

Magnetic ISO 7811 (Track I, II, III Read / Write),

HiCo/LoCo, JIS II

Contact Smartcard • ISO 7816 (ID -1)

Contactless Smartcard • MIFARE, ISO 14443 (Type A / B), (Internal & External) ISO 15693, DESFIRE, iCLASS

Certifications • CE, FCC, KCC



OFFICE Room 601, 7th Byuck-San Digital Valley, 170-13
 Guro-Dong, Guro-Gu, Seoul 152-742, Korea

●T E L 82-2-6099-3700 ●F A X 82-2-6099-3717

•E-mail sales@idp-corp.com



Smart, Smarter than any other ID Card Printer



